


Declaration of Performance

DoP-CPR- 18-3572

1. Unique identification code of the product, product type or product family: Collection: Artisan Type: 02 Designs: Articles: Drift, Fringe, 40300-40316, 40320-40324, Twill, Bandeau, 40330-40333, 40340-40345, Shimmer, Fraction 40350-40355, 40360-40362																																																		
2. Identification of the product: Type, batch or serial number: See packing label																																																		
3. The product(s) are intended for use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15102:2007+A1:2011: Wallcovering for decorative use																																																		
4. Name and contact address of the manufacturer: <div style="float:right; text-align: right;"> Arte NV Industriezone "De Waerde" Senator A. Jeurissenlaan 1210 BE-3520 Zonhoven T +32 (0) 11 81 93 00 F +32 (0) 11 81 93 01 info.belgium@arte-international.com </div>																																																		
5. Name and contact address of authorised representative (distributor, importer): Not applicable																																																		
6. System of assessment and verification of constancy of performance: System 3																																																		
7. Notified testing laboratory Centexbel performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer) and issued the test report(s): Certification report Centexbel : 19/745																																																		
8. Declared performance: <table border="1" style="width:100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width:25%;">Essential Characteristic</th> <th style="width:25%;">Performance</th> <th style="width:10%;">Harmonised technical specification</th> <th style="width:25%;">Essential Characteristic</th> <th style="width:10%;">Performance</th> <th style="width:15%;">Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire EN 13501-1</td> <td>B-S1,d0</td> <td rowspan="8" style="text-align: center; vertical-align: middle;">EN 15102:2007 A1:2011</td> <td>Release of vinyl chloride monomer EN 12149-B</td> <td style="text-align: center;">< 0.2 mg/kg</td> <td rowspan="4" style="text-align: center; vertical-align: middle;">EN 15102:2007 A1: 2011</td> </tr> <tr> <td>Release of formaldehyde EN 12149-C</td> <td style="text-align: center;">< 120 mg / kg</td> <td>Sound absorption ISO 354</td> <td style="text-align: center;">NPD</td> </tr> <tr> <td rowspan="4">Release of heavy metals (EN 12149-A)</td> <td>Anitimony < 0.1 mg/kg</td> <td>Thermal resistance "EN 12524" or "EN12667"</td> <td style="text-align: center;">NPD</td> </tr> <tr> <td>Arcenic < 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Barium < 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Cadmium < 0.3 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Chromium < 0.1 mg/kg</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Lead < 0.5 mg/kg</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Mercury < 0.1 mg/kg</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Selenium < 1.0 mg/kg</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification	Reaction to fire EN 13501-1	B-S1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011	Release of formaldehyde EN 12149-C	< 120 mg / kg	Sound absorption ISO 354	NPD	Release of heavy metals (EN 12149-A)	Anitimony < 0.1 mg/kg	Thermal resistance "EN 12524" or "EN12667"	NPD	Arcenic < 0.1 mg/kg			Barium < 0.1 mg/kg			Cadmium < 0.3 mg/kg			Chromium < 0.1 mg/kg				Lead < 0.5 mg/kg				Mercury < 0.1 mg/kg				Selenium < 1.0 mg/kg			
Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification																																													
Reaction to fire EN 13501-1	B-S1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011																																													
Release of formaldehyde EN 12149-C	< 120 mg / kg		Sound absorption ISO 354	NPD																																														
Release of heavy metals (EN 12149-A)	Anitimony < 0.1 mg/kg		Thermal resistance "EN 12524" or "EN12667"	NPD																																														
	Arcenic < 0.1 mg/kg																																																	
	Barium < 0.1 mg/kg																																																	
	Cadmium < 0.3 mg/kg																																																	
Chromium < 0.1 mg/kg																																																		
Lead < 0.5 mg/kg																																																		
Mercury < 0.1 mg/kg																																																		
Selenium < 1.0 mg/kg																																																		
* NPD: No Performance Declared																																																		
Signed for and behalf of the manufacturer or authorised representative by: <div style="text-align: right; margin-top: 20px;">  </div>																																																		
11-Apr-22		Philippe Desart		Managing Director																																														