

# ARTE®

wallcoverings for the ultimate in refinement

[www.arte-international.com](http://www.arte-international.com)


COLLECTION **SIENNA**

LUXURIOUS 54" VINYL WALLCOVERINGS FOR THE CONTRACT MARKET

Pattern  
References

**GALUCHAT**  
47180 - 47194


	<b>U.S. Units</b>	<b>Metric Units</b>
Total weight	24 oz. PLY 16 oz. PSY	742 g PLM 542 g m <sup>2</sup>
Roll width	54/55 in.	137/140 cm
Nominal pattern width	52 in.	132 cm
Gauge (average)	0.026 in.	0.66 mm
Fabric	Non-woven	
Repeat	horizontal	13 in.      33 cm
	vertical	13 in.      33 cm
Hanging instructions	Non-reverse – Align pattern horizontally and vertically – cut seam through center of diamonds	



FACT SHEET

COLLECTION SIENNA

Pattern  
References GALUCHAT  
47180 - 47194



## GENERAL SPECIFICATIONS

**IMPORTANT:** read the hanging instructions before starting the installation.

### EU CLASSIFICATION

in accordance with EN 13501-1: 2007 and prEN 15102: 2004

Fire Behavior B  
Smoke Production s2  
Flame Droplets d0

### US CLASSIFICATION

Tensile (minimum): 50 x 50 lbf 222 x 222 N  
Tear (minimum): 25 x 25  
ASTM F-793 : Category V Type II  
WA Spec: W 101 - 2011 Type II

Fire Testing:

NFPA 101® Life Safety Code®

NFPA 255 (UL723, CAN S102M) Tunnel Test<sup>1</sup>

- Class A Rating

NFPA 286 Corner Burn Test<sup>2</sup>

Meets requirements for Flame Spread, Smoke Developed and Flashover.

1. When tested on GRC board with A-848-B adhesive

2. When tested on 5/8" Type X gypsum board with A-848-B adhesive

Galuchat # 47183 - # 47185 - # 47187 - # 47188 - # 47189 - # 47190 - # 47191 - # 47192 - # 47193 - # 47194  
These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners and/or excessive scrubbing, have the potential to damage the surface of the wallcovering.

Notes:

- "Roll Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.

- "Gauge" is the product thickness measured after the first pattern colourway is produced.

- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.

- "Nominal Pattern Width" is the expected width yield from one drop on the wall.



1408/13

Product complying with the Marine Equipment Directive (MED)

ARTE®

www.arte-international.com